

GTS26S

单12寸超低频音箱
Single 12 inch Subwoofer

GTS SERIES




应用范围 Application

- ▶ 大会议厅、中小型多功能厅主扩声、中小型流动演出主扩声、大型扩声系统辅助扩声
- ▶ Main sound for Large conference hall, Small and medium sized multi-function hall, main sound of small and medium-sized touring performance, and supporting fills of large-scale sound-amplifying system

产品特性 Features

- ▶ GTS26S是一款单12寸紧凑型线阵列低频音箱,拥有高声压级输出和高保真扩声性能,搭配GTS26线阵列音箱组合吊挂或地面组合堆叠式使用,配置了两个力学优化式抽手,表面采用聚脲喷涂工艺,更结实耐磨。
- ▶ GTS26S is single 12-inch compact line array active subwoofer, with high sound pressure level output and high-fidelity sound reinforcement performance. The system can be hanged or stacked on the ground. Speaker box equipped with two handles, and adopts polyurea coating process, which is more strong and wear-resistant.

产品尺寸 Product dimension



参数规格 Specifications

系统类型	单12寸超低频音箱	System type	Active Single 12 inch Subwoofer
灵敏度(1W/1m)	96dB	Sensitivity(1W/1m)	96dB
频率响应	40Hz-300Hz(±3dB)/35Hz-350Hz(-10dB)	Frequency response	40Hz-300Hz(±3dB)/35Hz-350Hz(-10dB)
额定功率(AES)	1000W	Power rating(AES)	1000W
最大声压级(连续/峰值)	125dB/131dB	SPL(continuous/peak)	125dB/131dB
标称阻抗	8Ω	Nominal Impedance	8Ω
低音单元	12寸低音(100芯4寸音圈)	LF	12"(100mm Voice coil)
连接件	2×NEUTRIK NL4MP四芯插座1+1-	connectors	2×Neutrik 4 PIN socket (1+ 1-)
尺寸(H×W×D)	349.5×534×540mm	Dimension(H×W×D)	349.5×534×540mm
重量	28.3kg	Weight	28.3kg



广州市锐丰智能科技有限公司 A: 广东省广州市番禺区市莲路石楼路段10号
T: 020-3928 0043 F: 020-39280123-8014 E: info@rfintell.com Z: 511447 www.rfintell.com

Guangzhou Ruifeng Intelligence Technology Co., Ltd Address: No. 10, Shilou Section, Shilian Road, Panyu District, Guangzhou, Guangdong, China
T: +86 2039280083 Mobile: +86 13609092324 F: +86-20-39280123-8014 E: mail:sales@rfintell.com Z: 511447 www.rfintell.com