



产品特性 Features

- ▶ 适用于UHF频段天线系统，此产品涵盖频率470-960MHz。
- ▶ 带有4个独立输出直流电源，可供4台无线接收机同时使用。
- ▶ 可以多台分配器级联使用。
- ▶ 精简金属外壳，1U标准机柜设计结构。
- ▶ 采用低噪声及低互调失真设计，能排除混频干扰。
- ▶ 2个BNC座定向天线输入口，可直接连接UA590I定向天线板。
- ▶ UHF antenna system, the frequency will be 470-960MHz.
- ▶ 4 individual outputs DC power supply for 4 wireless receivers to operate simultaneously.
- ▶ Multiple distributor cascading application.
- ▶ 1U standard metal cabinet.
- ▶ Low noise and low intermodulation distortion design could eliminate mixed frequency interference.
- ▶ 2 BNC seat directive antenna inputs can be directly connect to UA590I antenna.

参数规格 Specifications

机箱规格	EIA标准1U	Cabinet specification	EIA standard 1U
频率范围	470-960MHz	Frequency range	470-960MHz
RF输出增益	0dB±1dB	RF output gain	0dB±1dB
输出三阶交调截取点	+38dBm	Output third order intermodulation intercept point	+38dBm
噪声指数	<1.5dB	Noise figure	<1.5dB
系统抗阻	50欧姆	System resistance	50 ohm
天线输入接头供电	12V/150mA DC	Antenna input connector power supply	12V/150mA DC
输出供电	每通道输出12V/1000MA DC	Output power supply	12V/1000MA DC per channel
主机供电	110—240V AC 50/60Hz	Host power supply	110—240V AC 50/60Hz
接头	BNC	Connector	BNC
尺寸(H×W×D)	45×482×220mm	Dimension	45×482×220mm
重量	2.075kg	Weight	2.075KG
功率	5W	Rating power	5W

