

专利号: ZL 2016301201154
ZL 201922296011.X




应用范围 Application

- ▶ 剧场、礼堂、演艺大厅主扩声、大会议厅、多功能厅主扩声、体育场馆扩声、中小型流动演出主扩声、大型扩声系统辅助扩声
- ▶ Stadium, Theatre, Auditorium, Banquet hall, Multi-function hall, Touring, Portable application

产品特性 Features

- ▶ VK208是一款紧凑, 被广泛应用的高性能阵列音箱, 采用2×8寸中低音, 1×3寸 (75mm音圈) 高音, 精选优质高效能配件, 高频细腻、通透, 低频厚实圆润有力; 大功率工作时失真小, 覆盖角度有较强的恒指向性, 声音听感一致性好等特点; 非常适合要求高清晰度的厅堂和流动演出使用。
- ▶ VK208配套吊架件, 每组可吊挂多达16只音箱, 具备7:1的安全系数。可吊挂安装、地面堆叠式安装等方式, 大大扩展了音箱的用途范围。
- ▶ VK208 is an ultra-compact design, broadly used high-efficiency line array speaker, The high quality 2×8" low and mid frequency drivers and a 1×3" high frequency driver with 75mm aluminium voice coil, The HF drivers provide a much smoother and more transparent high frequency response, whilst minimising distortion, especially at high sound pressure levels, The dispersion has strong constant directivity, with uniform sound cover, Suitable for halls demanding high definition and touring.
- ▶ The integrated rigging system has a 7:1 safety coefficient, Designed to be hanging or ground stacked in various array configurations.







声波导向相位塞

提高低音驱动器中低频的可用输出, 增加灵敏度, 提高声压级和改善指向性, 提高音箱低音驱动单元水平及垂直分频点。

Sound wave guide phase plug technology

It enhances MF&LF output of Low frequency driver, increases sensitivity, improve sound pressure level and directivity, boost the horizontal and vertical crossover of the LF unit.

产品尺寸 Product dimension



参数规格 Specifications

系统类型	双8寸二分频二驱动曲线阵列音箱	System type	Dual 8" Two-Way Bi-Amp Line Array Speaker
灵敏度(1W/1m)	HF:110dB LF:98dB	Sensitivity(1W/1m)	HF:110dB LF:98dB
频率响应	85Hz~17kHz(±3dB)/80Hz~18kHz(-10dB)	Frequency response	85Hz~17kHz(±3dB)/80Hz~18kHz(-10dB)
额定功率(AES)	HF:75W LF:300W	Power rating(AES)	HF:75W LF:300W
最大声压级(连续/峰值)	128.7dB/134.7dB	SPL(continuous/peak)	128.7dB/134.7dB
覆盖角度(H×V)	120°×10°	Dispersion(H×V)	120°×10°
标称阻抗	HF:16Ω LF:16Ω	Nominal Impedance	HF:16Ω LF:16Ω
分频点	1.5kHz	Crossover	1.5kHz
低音单元	2×8寸中低音	LF	2×8" low/mid frequency driver
高音单元	1×3寸(75mm高音)	HF	1×3" (75mm voice coil)
连接件	2×NEUTRIK NL4MP四芯插座, HF:2+ 2-, LF:1+ 1-	Connectors	NEUTRIK NL4MP×2 HF:2+ 2-, LF:1+ 1-
尺寸(H×W×D)	254×526×480mm (不含插销)	Dimension(H×W×D)	254×526×480mm (without pin)
重量	26kg	Weight	26kg



广州市锐丰智能科技有限公司 A: 广东省广州市番禺区市莲路石楼路段10号
T: 020-3928 0043 F: 020-39280123-8014 E: info@rfintell.com Z: 511447 www.rfintell.com

Guangzhou Ruifeng Intelligence Technology Co., Ltd Address: No.10, Shilou Section, Shilian Road, Panyu District, Guangzhou, Guangdong, China
T: +86 2039280083 Mobile: +86 13609092324 F: +86-20-39280123-8014 E: mail:sales@rfintell.com Z: 511447 www.rfintell.com

