



产品特性 Features

- 网页控制：配合WIFI或有线组成的局域网，可使用移动设备，以网页形式对主机进行控制，可使用输入主机IP地址或二维码扫码方式登陆。
 - 短信发送：可通过网页，对指定的单元或全部单元发送文字信息，实现会场通知功能，并可通过网页删除所有信息。
 - 服务项目：通过网页，可以自定义设置单元上的6个服务项目名称，并可通过服务专用账号与密码登陆服务网页，完成单元的服务项目响应与内容删除。
 - 触控屏操作：主机具有4.3寸全视角高清IPS彩屏，配以电容触屏，使其操作更容易直观，省去传统机械按键的寿命与灰尘问题。
 - 中控操作：具有单独发码与收码两个RS232端口，两个端口可同时工作，更符合智能会议室的要求，使用发码端口，可实现摄像跟踪与语音识别、语音翻译操作；收码端口，可使用中控系统对主机进行开关话筒、模式转换等操作。
 - USB录音：接入U盘，可对会议进行实时录音，并可播放U盘中储存的会议录音文件。
 - 视像跟踪：主机不需其他外配设备即可完成视像跟踪设置，系统支持EVI-D70、PELCO-D、PELCO-P协议，当摄像机数量超过2个时，需摄像机具有级联功能，或者使用中控系统实现。
 - 发言模式：具有先进先出、后进先出、讨论模式、自动模式、主席模式、全开模式、发言人数可设置在1-12人。
 - 发言时间：有两种时间限制，一是语音等待时间，设置时间后，会限定时间内话筒没拾取到声音会自动关闭话筒，如其间拾取到声音会重新计时；二是会议发言时间，在达到设置时间后，会强制关闭话筒发言。
 - 话筒航空接口：4路话筒接口，每路可支持15支话筒，接头带螺母锁定，保证每个接口牢固可靠。
 - 声控系统：有声控开启单元功能，当话筒拾取到声音后会自动打开单元，可调节其灵敏度控制打开话筒所需的音量。
 - 签到投票：可通过主机、PC网页、主席单元三种方式发起简单的签到投票功能，如需使用全功能签到投票功能，可使用PC表决专用软件，连接方式为局域网。
 - 级联无线投票系统：可通过交换机将会议主机与无线投票主机进行级联，使用PC表决软件将其数据融合，现实有线与无线签到投票的整合。
 - 同声传译：主机提供1路同声传译功能，使用专用的翻译话筒与翻译通道连接，其他单元可以选择收听原声通道或是翻译通道（需耳机收听）。
 - 话筒扩展器：配合话筒扩展主机，可将系统话筒容量扩容到250支单元。
- Website Control: mobile devices control are available through webpage by WIFI and internet.
- Message Delivery: word message could be sent or deleted to all units or specified units by webpage.
- Service Item: 6 service items of the unit could be modified through webpage.
- Touch Screen: 4.3" IPS display with touchable screen for more directly control.
- Central Control: individual code sending and code receiving.
- USB Record: real-time recording for conference by USB disk.
- Visual Tracking: EVI-D70、PELCO-D、PELCO-P are available.
- Speech Mode: first in first out, last in first out, discussion mode, auto mode and all open mode.
- Microphone air interface: 4 channel microphone interfaces could support 15 microphones per channel.
- Voice control system: when the microphone picks up the sound, it will automatically turn on and the sensitivity can be adjusted to control the volume required .
- Sign and vote: the host could realize sign and vote function through the web page and the chairman unit. If you need to use the full-function sign and vote function, you could apply the PC voting software, and the connection mode is LAN.



LH-800M

会议主机

Conference Host

LH SERIES

参数规格 Specifications

话单元接口	8P航空插座4个	Microphone connector	8P aerial socket*4
翻译单元接口	8P航空插座1个	Translation connector	8P aerial socket*1
扩展主机接口	8P航空插座1个	Extension connector	8P aerial socket*1
中控接口	RS232串口2个	Central control connector	RS232*1
摄像机接口	8P S端子1个, 485接口1个	Camera connector	8PS*1, 485*1
音频输出	XLR卡依插座1个, RCA插座1个	Audio output	XLR, RCA
音频输入	RCA插座1个	Audio input	RCA
TCP/IP接口	RJ45网口1个	TCP/IP connector	RJ45
视频切换接口	RS232串口1个	Video switch connector	RS232
录音接口	USB接口1个	Recording connector	USB
电压	AC 220V 50Hz	Voltage	AC 220V 50Hz
功率	120W	Power rating	120W
灵敏度	-15dB	Sensitivity	-15dB
频率响应	20Hz – 20kHz	Frequency response	20Hz – 20kHz
信噪比	104dB	SNR	104dB
尺寸 (W×D× H)	483×323×90mm	Dimension (W×D×H)	483×323×90mm



广州市锐丰智能科技有限公司 A:广东省广州市番禺区市莲路石楼路段10号

T:020-3928 0043 F:020-39280123-8014 E:info@rfintell.com Z:511447 www.rfintell.com

Guangzhou Ruifeng Intelligence Technology Co., Ltd Address: No.10, Shilou Section, Shilian Road, Panyu District, Guangzhou, Guangdong, China

T:+86 2039280083 Mobile: +86 13609092324 F:+86-20-39280123-8014 E: mail:sales@rfintell.com Z:511447 www.rfintell.com





产品特性 Features

- ▶ 触控屏操作：主机具有4.3寸全视角高清IPS彩屏，配以电容触屏，使其操作更容易直观，话筒开关支持触屏打开与机械打开两种方式，触屏方式可以避免由于机械开关所产生的物理声音传输到拾音头，机械开关让操作人员具有最传统的操作体验。
- ▶ 耳机端口：耳机端口支持单边耳机与双声道耳机，可在会议原声通道与翻译通道之间选择，可单独调音量或主机统一设置音量。
- ▶ 带灯开关：话筒的机械开关，在打开时会显示亮光，可直观显示当前状态。
- ▶ 抗干扰：对手机信号或其他干扰信号有超强的抗干扰能力。
- ▶ 分离式设计：话筒与底座使用分离式设计，可按使用要求更换不同的话筒杆。
- ▶ 主席功能：主席单元可安装在任何位置上，其优先键可关闭或暂停正在发言的代表单元。
- ▶ 恢复发言：当代表单元被主席单元关闭可，可以选择是手动打开，还是自动恢复发言。
- ▶ Touching screen: 4.3" IPS touching screen for easy operation. The microphone switch supports both touch screen and mechanical turn-on.
- ▶ Phone Port: The phone port supports unilateral headphone and dual-channel headphone, which can be selected between the conference soundtrack channel and the translation channel. The volume can be adjusted separately or the host can set the volume uniformly.
- ▶ Light switch: mechanical switch of the microphone flash in operation, which can visually display the status.
- ▶ Anti-interference: Powerful anti-interference function to mobile signal
- ▶ Separate design: the microphone and the base separate so it is easy for changing different microphone rods.

参数规格 Specifications

连接线	1.3米连接线	Connect cable	1.3m
话筒输入	4芯插座1个	MIC input	4pin socket
显示屏	4.3寸全视角触控彩屏	Display	4.3" touching screen
耳机输出	3.5mm耳机座1个	Phone output	3.5mm headphone
连接线	内置连接80cm	Connect cable	80cm
电源	DC 24V	Power	DC 24V
电流	130MA	Current	130MA
灵敏度	-50dB/Pa	Sensitivity	-50dB/Pa
频率响应	100Hz – 12kHz	Frequency response	100Hz – 12kHz
信噪比	70dB	SNR	70dB



LH-800I

翻译单元

Translation Unit

LH SERIES



产品特性 Features

- ▶ 触控屏操作：主机具有4.3寸全视角高清IPS彩屏，配以电容触屏，使其操作更容易直观，话筒开关支持触屏打开与机械打开两种方式。
- ▶ 耳机端口：耳机端口支持单边耳机与双声道耳机，只可以收听会议原声通道的声音。
- ▶ 带灯开关：话筒的机械开关，在打开时会显示亮光，可直观显示当前状态。
- ▶ 抗干扰：对手机信号或其他干扰信号有超强的抗干扰能力。
- ▶ 分离式设计：话筒与底座使用分离式设计，可按使用要求更换不同的话筒杆。
- ▶ 翻译通道：话筒的音频不会在扩声中输出，只可以在主席与代表单元的耳机中收听。
- ▶ Touching screen: 4.3" IPS touching screen for easy operation. The microphone switch supports both touch screen and mechanical turn-on.
- ▶ Phone Port: The phone port supports unilateral headphone and dual-channel headphone, which can be selected between the conference soundtrack channel and the translation channel. The volume can be adjusted separately or the host can set the volume uniformly.
- ▶ Light switch: mechanical switch of the microphone flash in operation, which can visually display the status.
- ▶ Anti-interference: Powerful anti-interference function to mobile signal
- ▶ Separate design: the microphone and the base separate so it is easy for changing different microphone rods.
- ▶ Translation Channel: The audio of the microphone will not be output in reinforcement. It can only be heard by the headset of the chairman and the representative unit.

参数规格 Specifications

连接线	1.3米连接线	Connect cable	1.3m
话筒输入	4芯插座1个	MIC input	4pin socket
显示屏	4.3寸全视角触控彩屏	Display	4.3" touching screen
耳机输出	3.5mm耳机座1个	Phone output	3.5mm headphone
连接线	内置连接80cm	Connect cable	80cm
电源	DC 24V	Power	DC 24V
电流	130MA	Current	130MA
灵敏度	-50dB/Pa	Sensitivity	-50dB/Pa
频率响应	100Hz – 12kHz	Frequency response	100Hz – 12KHz
信噪比	70dB	SNR	70dB



广州市锐丰智能科技有限公司 A: 广东省广州市番禺区市莲路石楼路段10号
T: 020-3928 0043 F: 020-39280123-8014 E: info@rfintell.com Z: 511447 www.rfintell.com
Guangzhou Ruifeng Intelligence Technology Co., Ltd Address: No.10, Shilou Section, Shilian Road, Panyu District, Guangzhou, Guangdong, China
T: +86 2039280083 Mobile: +86 13609092324 F: +86-20-39280123-8014 E: mail:sales@rfintell.com Z: 511447 www.rfintell.com

