

G50S

电容话筒
Condenser Microphone

产品特性 Features

- ▶带150Hz高通滤波。
- ▶48V幻象供电，室内、户外使用自如。
- ▶配备宽广均衡的频率响应范围。
- ▶特配以镀金的XLR连接片，使音频电流得到理想传输。
- ▶With 150Hz High Pass filtering.
- ▶48V phantom power used in indoor and outdoor.
- ▶With broad balanced range of frequency response.
- ▶The gold plated XLR link makes audio frequency current with ideal transmission.

参数规格 Specifications

单体	背极式驻极体	Element	Back Electret Condenser
指向性	超心型	Polar Pattern	Hyper-cardioid
频率范围	30Hz-18KHz (±3dB)	Frequency Response	30Hz-18KHz (±3dB)
灵敏度 (48V/1.5V)	-29dB ±3dB (1dB=1V/Pa at 1KHz)	Sensitivity (48V/1.5V)	-29dB ±3dB (1dB=1V/Pa at 1KHz)
输出阻抗	600Ω ±20% (at 1KHz)	Output Impedance	600Ω ±20% (at 1KHz)
最大声压级	130dB (T.H.D≤1% at 1KHz)	Max.Input SPL	130dB (T.H.D≤1% at 1KHz)
信噪比	72dB (1KHz at 1Pa) (A-Weighted)	SNR	72dB (1KHz at 1Pa) (A-Weighted)
等效噪声级	≤25dBa	Equivalent Noise Level	≤25dBa
使用电源	48V DC	Power Requirements	48V DC
开关	高通滤波 150Hz	Switch	High Pass filtering 150Hz
重量	69.7g (不含附件)	Weight	69.7g (without accessories)
本体尺寸	20×100mm	Dimension	20×100mm
输出接口	XLRM 三针公卡侬	Output Interface	XLRM3PIN male Cannon

